

01 Chechweighers



Principle: Dynamic online weighing and overweight & underweight rejection.

Function:

It is used for checking if the finished products are within the preset standard weight range, and automatically reject the substandard ones by dynamic weighing and control system.

Features:

1. Humanized structure design, easy to operate and clean.
2. Automatic zero tracking.
3. Flexible adjustment, applicable to products of multi specification range.
4. Resolution up to 16 bit weight measurement with 0.05% high accuracy.
5. 100 products parameters can be preset and called out.
6. High precision original Germany HBM digital load cell.
7. Rejection method: airjet, flapper, pusher and sliding for choice.
8. Weighing data output: RS232/485, USB, wireless data transmission, local network station management platform, cloud platform



Model	DHCW-300*80	DHCW-300*150
Capacity	100g	500g
Accuracy	±0.1g	±0.2g
Speed	150 pcs/min	150 pcs/min
Weighing belt size	L300*W80 mm	L300*W150 mm
Applicable product size	L150*W50 mm	L150*W120 mm
Belt conveyor	Food grade PU belt	
Power supply	AC200-220V, 50/60 Hz	
Control system	Dahang (Independent R & D)	
Construction	304 SUS304, polishing	
Height of conveyor	Customized	
Operation display	8 inches touch screen	
HS code	8423201000	
Package	Professional export plywood case	



Model	DHCW-400*150	DHCW-400*200	DHCW-500*200	DHCW-500*300
Capacity	1000g	1000g	3000g	5000g
Accuracy	±0.5g	±0.5g	±1g	±1-2g
Speed	120 pcs/min	120 pcs/min	120 pcs/min	120 pcs/min
Weighing belt size	L400*W150 mm	L400*W200 mm	L500*W200 mm	L500*W300 mm
Applicable product size	L200*W120 mm	L200*W150 mm	L300*W150 mm	L300*W250 mm
Belt conveyor	Food grade PU belt			
Power supply	AC200-220V, 50/60 Hz			
Control system	Dahang (Independent R & D)			
Construction	304 SUS304, polishing			
Height of conveyor	Customized			
Operation display	8 inches touch screen			
HS code	8423201000			
Package	Professional export plywood case			

Model	DHCW-600*300	DHCW-600*400	DHCW-700*500	DHCW-800*600
Capacity	5kg	10kg	30kg	50kg
Accuracy	±3g	±5g	±10g	±20g
Speed	60-120 pcs/min	60 pcs/min	60 pcs/min	30 pcs/min
Weighing belt size	L600*W300 mm	L600*W400 mm	L700*W500 mm	L800*W600 mm
Applicable product size	L400*W250 mm	L400*W350 mm	L500*W450 mm	L600*W550 mm
Belt conveyor	PVC belt			
Power supply	AC200-220V, 50/60 Hz			
Control system	Dahang (Independent R & D)			
Construction	304 SUS304, polishing			
Height of conveyor	Customized			
Operation display	8 inches touch screen			
HS code	8423201000			
Package	Professional export plywood case			





Carton box checkweigher



Food checkweigher



Bottle checkweigher